

Projekt: pora nocna

Dane do obliczeń :

•ród³a punktowe

Nr	X[m]	Y[m]	z[m]	Pma	Symbol
1	350.1	259.1	0.3	74.3	SO
2	363.8	250.4	0.3	74.3	SO
3	383.1	239.0	0.3	74.3	SO
4	342.0	246.5	0.3	74.3	SO
5	357.4	236.4	0.3	74.3	SO
6	374.2	223.6	0.3	74.3	SO
7	331.9	234.2	0.3	74.3	SO
8	344.8	224.7	0.3	74.3	SO
9	359.6	214.6	0.3	74.3	SO
10	313.4	235.9	0.3	74.3	SO
11	309.2	230.0	0.5	71.2	SC
12	320.1	245.7	0.5	71.2	SC
13	328.2	260.2	0.5	71.2	SC
14	338.9	276.5	0.5	71.2	SC
15	334.1	290.2	0.5	71.2	SC
16	355.1	276.8	0.5	71.2	SC
17	321.8	273.7	0.5	71.2	SC
18	345.9	288.2	0.5	71.2	SC
19	316.5	263.0	0.5	71.2	SC
20	338.3	264.4	0.5	71.2	SC
21	343.6	305.0	0.5	85.8	WW
22	354.8	296.9	0.5	85.8	WW
23	370.5	286.0	0.5	85.8	WW
24	384.2	276.5	0.5	85.8	WW
25	399.6	268.1	0.5	85.8	WW
26	371.7	275.3	0.5	85.8	WW
27	393.6	317.9	12.3	84.0	WD
28	369.6	329.6	12.3	84.0	WD
29	378.1	342.1	12.3	84.0	WD
30	386.7	354.7	12.3	84.0	WD
31	395.2	367.2	12.3	84.0	WD
32	403.8	379.8	12.3	84.0	WD
33	412.3	392.3	12.3	84.0	WD
34	420.9	404.9	12.3	84.0	WD
35	423.2	353.6	12.3	84.0	WD
36	445.9	391.3	12.3	84.0	WD
37	408.2	332.9	12.3	84.0	WD
38	410.8	300.8	12.3	84.0	WD
39	419.6	313.6	12.3	84.0	WD
40	428.3	326.3	12.3	84.0	WD
41	437.1	339.1	12.3	84.0	WD
42	445.9	351.9	12.3	84.0	WD
43	454.7	364.7	12.3	84.0	WD
44	463.4	377.4	12.3	84.0	WD
45	431.3	369.1	12.3	84.0	WD
46	435.2	377.9	12.3	84.0	WD
47	377.8	260.8	10.5	70.0	CW
48	364.4	265.6	10.3	73.0	JK

```

49 369.4 261.6 10.3 73.0 JK
50 374.4 258.6 10.3 73.0 JK
51 380.6 254.9 10.3 73.0 JK
52 388.2 249.9 10.3 73.0 JK
=====
    
```

•ród³a typu hala produkcyjna :

WSPÓŁRZĘDNE WIERZCHOŁKÓW :

Nr	X1[m]	Y1[m]	X2[m]	Y2[m]	X3[m]	Y3[m]	X4[m]	Y4[m]	h0[m]	h[m]
1	343.4	316.2	430.1	446.7	496.3	401.0	409.0	271.7	0.0	12.0
2	390.0	386.0	376.2	394.8	399.8	430.2	413.4	421.0	0.0	7.0

POZIOMY HAŁASU i IZOLACYJNOŚĆ PRZEGRÓD

Nr	Źród³a	A	63	125	250	500	1000	2000	4000	8000	wsp.odb.	
1	sc.1	L wew	80.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
		R sc	32.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
	sc.2	L wew	80.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
		R sc	32.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
	sc.3	L wew	80.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
		R sc	32.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
	sc.4	L wew	80.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
		R sc	32.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
	dach	L wew	80.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
		R d	32.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	

Nr	Źród³a	A	63	125	250	500	1000	2000	4000	8000	wsp.odb.	
2	sc.1	L wew	90.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
		R sc	32.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
	sc.2	L wew	90.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
		R sc	32.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
	sc.3	L wew	90.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
		R sc	32.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
	sc.4	L wew	90.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
		R sc	32.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
	dach	L wew	90.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
		R d	32.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	

Ekranu akustyczne :

WSPÓŁRZĘDNE WIERZCHOŁKÓW :

Nr	X1[m]	Y1[m]	X2[m]	Y2[m]	X3[m]	Y3[m]	X4[m]	Y4[m]	h0[m]	h[m]
1	343.6	316.6	389.8	386.4	382.0	391.2	335.2	321.4	0.0	7.0
2	364.2	277.4	358.0	267.2	392.2	244.4	398.0	254.4	0.0	10.0
3	522.8	245.8	542.0	317.3	606.3	299.5	586.6	229.0	0.0	6.0
4	567.0	233.3	553.0	180.0	572.7	175.2	585.7	229.4	0.0	6.0

WSPÓŁCZYNNIKI ODBICIA DLA ŚCIAN

Nr	ściana 1	ściana 2	ściana 3	ściana 4	dach
1	1.0000	1.0000	1.0000	1.0000	1.0000

2	1.0000	1.0000	1.0000	1.0000	1.0000
3	1.0000	1.0000	1.0000	1.0000	1.0000
4	1.0000	1.0000	1.0000	1.0000	1.0000

=====

Punkty obserwacji

Nr	Symbol	X [m]	Y [m]	z [m]
1		395.2	468.0	4.0
2		588.0	466.6	4.0
3		493.9	458.4	4.0

-----